



CONTACT DETAIL

1. CONTACT PLATING  
MATING AREA: 0.76 MICRO METERS MINIMUM GOLD PLATING  
TERMINATION AREA: 0.05 MICRO METERS MINIMUM GOLD PLATING  
UNDERPLATING: NICKEL PLATING
2. APPLICABLE HOOD  
HDR-26LPH ( )
3. MATING CONNECTOR  
HDR-EA26LMY ( ) G1+  
HDR-E26M ( ) G1+
4. SPECIFICATION  
RATED CURRENT 0.5A  
RATED VOLTAGE 125V AC (r. m. s.)

HONDA TSUSHIN KOGYO CO., LTD.  
 The product information in this data is for reference only.  
 This is subject to change without notice.  
 Contact our sales staff for further information before considering or ordering any of our products.  
 Please request the Engineering Drawing for the most current and accurate design information.

LTR.	DATE	BY	REV.	DESCRIPT	No.	PART NAME	MATERIAL	QTY	FINISH	NOTE	
					4	SPACER	PA9T (GF)	1	—	UL94V-0 BLACK	
					3	INSULATOR	PA9T (GF)	1	—	UL94V-0 BLACK	
					2	SHELL	STEEL	1	NICKEL PLATING	—	
					1	FEMALE CONTACT	PHOSPHOR BRONZE	26	NOTE#1	—	
DATE					SCALE	UNIT	3RD. A. P				
Feb. 22, 2007					3 / 1	mm (INCH)	HONDA TSUSHIN KOGYO CO., LTD.				
APP. DATE & REV.					DR.	DE.	CHK.	CHK.	APP.	NAME	0.8mm SPACING SHIELDED FEMALE CABLE CONNECTOR (RoHS)
					Y. KATO	Y. KATO	—	C. NUNOKAWA	H. EBIHARA	PART NO.	HDR-E26FSG1+
										REV.	