



CONTACT DETAIL

1. CONTACT PLATING
 MATING AREA: 0.76 MICRO METERS MINIMUM GOLD PLATING
 TERMINATION AREA: 0.05 MICRO METERS MINIMUM GOLD PLATING
 UNDERPLATING: NICKEL PLATING
2. APPLICABLE HOOD
 HDR-26LPH ()
3. MATING CONNECTOR
 HDR-EA26LMY () G1+
 HDR-E26M () G1+
4. SPECIFICATION
 RATED CURRENT 0.5A
 RATED VOLTAGE 125V AC (r. m. s.)

LTR.	DATE	BY	REV.	DESCRIPT	No.	PART NAME	MATERIAL	QTY	FINISH	NOTE
					4	SPACER	PA9T (GF)	1	—	UL94V-0 BLACK
					3	INSULATOR	PA9T (GF)	1	—	UL94V-0 BLACK
					2	SHELL	STEEL	1	NICKEL PLATING	—
					1	FEMALE CONTACT	PHOSPHOR BRONZE	26	NOTE#1	—
DATE					SCALE	UNIT	3RD. A. P			
Feb. 22, 2007					3 / 1	mm (INCH)	HONDA TSUSHIN KOGYO CO., LTD.			
APP. DATE&REV.					NAME		0.8mm SPACING SHIELDED FEMALE CABLE CONNECTOR (RoHS)			
DR.	DE.	CHK.	CHK.	APP.	PART NO.		HDR-E26FSG1+			
Y. KATO	Y. KATO	—	C. NUNOKAWA	H. EBIHARA			REV.			